

Lamp Chart

4' Nominal Length

Please verify with ballast manufacturer(s) to ensure specific lamp/ballast compatibility.					
Lamp Mfg	Lamp Mfg's Catalog Number	Nominal Wattage	Lumen Rating	Peerless Code	
GE	F32T8/25WSPX30EC	25	2400	G830E25	T8
GE	F32T8/25WSPX35EC	25	2400	G835E25	
GE	F32T8/25WSPX41EC	25	2400	G841E25	
Osram/Sylvania	FO32/25W/830/XP/SS/ECO3	25	2400	S830E25	
Osram/Sylvania	FO32/25W/835/XP/SS/ECO3	25	2400	S835E25	
Osram/Sylvania	FO32/25W/841/XP/SS/ECO3	25	2400	S841E25	
Philips	F32T8 25W ADV830 XEW ALTO	25	2475	P830E25	
Philips	F32T8 25W ADV835 XEW ALTO	25	2475	P835E25	
Philips	F32T8 25W ADV841 XEW ALTO	25	2475	P841E25	
GE	F28T8/SP30/UMX/ECO	28	2750	G830E28	
GE	F28T8/SP35/UMX/ECO	28	2750	G835E28	
GE	F28T8/SP41/UMX/ECO	28	2750	G841E28	
Osram/Sylvania	FO28/830/XP/SS/ECO	28	2725	S830E28	
Osram/Sylvania	FO28/835/XP/SS/ECO	28	2725	S835E28	
Osram/Sylvania	FO28/841/XP/SS/ECO	28	2725	S841E28	
Philips	F32T8 28W ADV830 EW ALTO	28	2725	P830E28	
Philips	F32T8 28W ADV835 EW ALTO	28	2725	P835E28	
Philips	F32T8 28W ADV841 EW ALTO	28	2725	P841E28	
GE	F32T8/SP30IS/WM/ECO	30	2850	G830E30	
GE	F32T8/SP35IS/WM/ECO	30	2850	G835E30	
GE	F32T8/SP41IS/WM/ECO	30	2850	G841E30	
Osram/Sylvania	FO30/830/XP/SS/ECO3	30	2850	S830E30	
Osram/Sylvania	FO30/835/XP/SS/ECO3	30	2850	S835E30	
Osram/Sylvania	FO30/841/XP/SS/ECO3	30	2850	S841E30	
Philips	F32T8 30W ADV830 EW ALTO	30	2850	P830E30	
GE	F32T8/XL/SPX30/HL/ECO	32	3100	G830HT8	
GE	F32T8/XL/SPX35/HL/ECO	32	3100	G835HT8	
GE	F32T8/XL/SPX41/HL/ECO	32	3100	G841HT8	

Lamp Chart

4' Nominal Length

Please verify with ballast manufacturer(s) to ensure specific lamp/ballast compatibility.					
Lamp Mfg	Lamp Mfg's Catalog Number	Nominal Wattage	Lumen Rating	Peerless Code	
GE	F32T8/SP30/ECO	32	2800	LPGM730	T8
GE	F32T8/SP35/ECO	32	2800	LPGM735	
GE	F32T8/SP41/ECO	32	2850	LPGM741	
GE	F32T8/XL/SP30ECO	32	2800	LPGM730EX	
GE	F32T8/XL/SP35ECO	32	2800	LPGM735EX	
GE	F32T8/XL/SP41ECO	32	2800	LPGM741EX	
GE	F32T8/SPX30/ECO	32	2950	LPGM830	
GE	F32T8/SPX35/ECO	32	2950	LPGM835	
GE	F32T8/SPX41/ECO	32	2950	LPGM841	
GE	F32T8/XL/SPX30/ECO	32	2950	LPGM830EX	
GE	F32T8/XL/SPX35/ECO	32	2950	LPGM835EX	
GE	F32T8/XL/SPX41/ECO	32	2950	LPGM841EX	
Peerless Choice	3000K 70CRI+ LAMP	32	2800	LP730	
Peerless Choice	3500K 70CRI+ LAMP	32	2800	LP735	
Peerless Choice	4100K 70CRI+ LAMP	32	2800	LP741	
Peerless Choice	3000K 80CRI+ LAMP	32	2950	LP830	
Peerless Choice	3500K 80CRI+ LAMP	32	2950	LP835	
Peerless Choice	4100K 80CRI+ LAMP	32	2950	LP841	
Peerless Choice	5000K 80CRI+ LAMP	32	2950	LP850	
Osram/Sylvania	FO32/730/ECO	32	2800	LPSM730	
Osram/Sylvania	FO32/735/ECO	32	2800	LPSM735	
Osram/Sylvania	FO32/741/ECO	32	2800	LPSM741	
Osram/Sylvania	FO32/730XP/ECO	32	2850	LPSM730EX	
Osram/Sylvania	FO32/735XP/ECO	32	2850	LPSM735EX	
Osram/Sylvania	FO32/741XP/ECO	32	2850	LPSM741EX	
Osram/Sylvania	FO32/830/ECO	32	2950	LPSM830	
Osram/Sylvania	FO32/835/ECO	32	2950	LPSM835	
Osram/Sylvania	FO32/841/ECO	32	2950	LPSM841	
Osram/Sylvania	FO32/830XP/ECO	32	3000	LPSM830EX	
Osram/Sylvania	FO32/835XP/ECO	32	3000	LPSM835EX	
Osram/Sylvania	FO32/841XP/ECO	32	3000	LPSM841EX	
Osram/Sylvania	FO32/830/XPS/ECO3	32	3100	S830HT8	
Osram/Sylvania	FO32/835/XPS/ECO3	32	3100	S835HT8	
Osram/Sylvania	FO32/841/XPS/ECO3	32	3100	S841HT8	
Philips	F32T8/TL730/ALTO	32	2800	LPPM730	

Lamp Chart

4' Nominal Length

Please verify with ballast manufacturer(s) to ensure specific lamp/ballast compatibility.					
	Lamp Mfg	Lamp Mfg's Catalog Number	Nominal Wattage	Lumen Rating	Peerless Code
T8	Philips	F32T8/TL735/ALTO	32	2800	LPPM735
	Philips	F32T8/TL741/ALTO	32	2800	LPPM741
	Philips	F32T8/TL830/ALTO	32	2950	LPPM830
	Philips	F32T8/TL835/ALTO	32	2950	LPPM835
	Philips	F32T8/TL841/ALTO	32	2950	LPPM841
	Philips	F32T8/ADV830/ALTO	32	3100	P830HT8
	Philips	F32T8/ADV835/ALTO	32	3100	P835HT8
	Philips	F32T8/ADV841/ALTO	32	3100	P841HT8
T5	Philips	F28T5/830/EA/ALTO 25W	25	2900	P830E25
	Philips	F28T5/835/EA/ALTO 25W	25	2900	P835E25
	Philips	F28T5/841/EA/ALTO 25W	25	2900	P841E25
	GE	F28W/T5/830/ECO	28	2900	LPGM830
	GE	F28W/T5/835/ECO	28	2900	LPGM835
	GE	F28W/T5/841/ECO	28	2900	LPGM841
	Peerless Choice	3000K 80CRI+ LAMP	28	2900	LP830
	Peerless Choice	3500K 80CRI+ LAMP	28	2900	LP835
	Peerless Choice	4100K 80CRI+ LAMP	28	2900	LP841
	Peerless Choice	3000K 80CRI+ LAMP	28	3050	LP830P
	Peerless Choice	3500K 80CRI+ LAMP	28	3050	LP835P
	Peerless Choice	4100K 80CRI+ LAMP	28	3050	LP841P
	Osram/Sylvania	FP28/830/ECO	28	2900	LPSM830
	Osram/Sylvania	FP28/835/ECO	28	2900	LPSM835
	Osram/Sylvania	FP28/841/ECO	28	2900	LPSM841
	Osram/Sylvania	3000K 80CRI+ LAMP	28	3050	LPSM830P
	Osram/Sylvania	3500K 80CRI+ LAMP	28	3050	LPSM835P
	Osram/Sylvania	4100K 80CRI+ LAMP	28	3050	LPSM841P
	Philips	F28T5/830/ALTO	28	2900	LPPM830
	Philips	F28T5/835/ALTO	28	2900	LPPM835
Philips	F28T5/841/ALTO	28	2900	LPPM841	
T5HO	Philips	F54T5/830/HO/EA/ALTO/49W	49	5000	P830E49
	Philips	F54T5/835/HO/EA/ALTO/49W	49	5000	P835E49
	Philips	F54T5/841/HO/EA/ALTO/49W	49	5000	P841E49

Lamp Chart

4' Nominal Length

Please verify with ballast manufacturer(s) to ensure specific lamp/ballast compatibility.					
Lamp Mfg	Lamp Mfg's Catalog Number	Nominal Wattage	Lumen Rating	Peerless Code	
GE	F54T5/830/WM/ECO	51	5000	G830E51	
GE	F54T5/835/WM/ECO	51	5000	G835E51	
GE	F54T5/841/WM/ECO	51	5000	G841E51	
Osram/Sylvania	FP54/51W/830/HO/SS/ECO	51	5000	S830E51	
Osram/Sylvania	FP54/51W/835/HO/SS/ECO	51	5000	S835E51	
Osram/Sylvania	FP54/51W/841/HO/SS/ECO	51	5000	S841E51	
T5HO	GE	F54W/T5/830/HO/ECO	54	5000	LPGM830
	GE	F54W/T5/835/HO/ECO	54	5000	LPGM835
	GE	F54W/T5/841/HO/ECO	54	5000	LPGM841
	Peerless Choice	3000K 80CRI+ LAMP	54	5000	LP830
	Peerless Choice	3500K 80CRI+ LAMP	54	5000	LP835
	Peerless Choice	4100K 80CRI+ LAMP	54	5000	LP841
	Peerless Choice	5000K 80CRI+ LAMP	54	5000	LP850
	Osram/Sylvania	FP54/830/HO/ECO	54	5000	LPSM830
	Osram/Sylvania	FP54/835/HO/ECO	54	5000	LPSM835
	Osram/Sylvania	FP54/841/HO/ECO	54	5000	LPSM841
	Philips	F54T5/830/HO/ALTO	54	5000	LPPM830
	Philips	F54T5/835/HO/ALTO	54	5000	LPPM835
	Philips	F54T5/841/HO/ALTO	54	5000	LPPM841

Notes:

1. 100 hour burn-in recommended for all dimming ballast applications.
2. Dimming ballast not recommended with low wattage T8 lamps (includes 25, 28 and 30W).
Striations will occur between 50% and 70% dimming.
3. 0.71 Ballast Factor ballasts not recommended with 25W T8 lamps.
4. Check with lamp manufacturer to verify lamp/ballast compatibility.